

High Speed Printing



Easy paper loading, convenient operation

- Direct Thermal Print
- High Speed Printing
- High Resolution
- Max. 80mm Print Width
- Auto-cutter
- Easy paper loading

Print	
Print method:	Direct Thermal
Resolution:	640 dots/line
Print speed:	260mm/s
Printing Width:	80mm(max)/72mm(default)
Sensors:	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)
Drivers:	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/ OPOS/JPOS
Interface:	Serial+USB+Lan/Serial+USB+Lan+Wifi/ Serial+USB+Lan+Bluetooth
Emulation:	ESC/POS
Barcodes Fonts	
Barcodes:	1D:UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/ CODE93/CODE128 2D: QR Code
Fonts:	Font A: 12x24 Font B: 9x17 Chinese: GB18030,BIG5 24x24dots Japanese/Korea: Support User-defined: Support
Paper	
Paper Type:	Thermal Receipt Paper
Paper width:	48mm/52mm/56mm/64mm/68mm/76mm/80mm
Paper Thickness:	0.06~0.08mm
Roll Dia:	Max. Ø 83 mm
Paper Cut:	Manual tear or Auto-cutter
Power supply	
Input:	AC 100V-240V 50/60HZ
Output:	DC 24V/2.5A
Reliability	
Printing head:	150KM
Cutter:	1.5 million cuts
Environment	
Working Condition:	0°C~45°C, 10%~80%RH
Storage Condition:	-10°C-60°C,10%~90%RH
Physics Spec.	
Dimensions:	191(D)x146(W)x129(H)mm
Net weight/Gross weight:	1.94kg/2.14kg
 	